

✓  
County Surveyor's Record, Douglas County, Oregon

6th Standard Parallel South of Tp. 27 S., R 1 E.

CHAINS	
	<p style="text-align: center;">dist. marked T 27 S R 1 E S 31 B T.</p> <p style="text-align: center;">A Fir, 8 ins. diam., bears S.45*W., 15 lks.</p> <p style="text-align: center;">dist. marked S B T.</p> <p>Land, 4th rate, mountainous rough and rocky</p> <p>Timber, Fir, Hemlock Spruce and Pine.</p> <p>Thick underbrush, Cinnamon, Vine Maple and Elk Brush.</p>
	<p>East, on South Boundary of Sec. 32</p> <p style="text-align: right;">Var. 18*30'E.</p>
36.25	Summit of Ridge N and S
40.00	<p>Set post, 44x4 ins. firmly in the ground for standard <math>\frac{1}{4}</math> sec. cor. marked S C on N and S faces, from which</p> <p style="text-align: center;">A Pine, 30 ins. diam., bears N.20*W., 38 lks.</p> <p style="text-align: center;">dist. marked S C <math>\frac{1}{4}</math> S B T.</p> <p style="text-align: center;">A Fir, 36 ins. diam., bears S.20*W., 53 lks.</p> <p style="text-align: center;">dist. marked S C <math>\frac{1}{4}</math> S B T.</p>
51.20	Spring branch, 2 lks. wide, course SE
63.90	Nickel Creek, 2 lks. wide, course South.
68.00	Offset N, 4 chs. 10 lks. to avoid rocky bluffs.
72.34	Came back to line again.
80.00	<p>Set post, 48x4 ins. firmly in the ground for standard cor. to secs. 32 and 33 marked S C T 27 S R 1 E on N, S 33 on E and S 32 on W faces, with 4 notches on E and 2 on W edges, from which</p> <p style="text-align: center;">A Fir, 18 ins. diam., bears N.20*E., 33 lks.</p> <p style="text-align: center;">dist. marked T 27 S R 1 E S 33 B T.</p> <p style="text-align: center;">A Fir, 24 ins. diam., bears N.23*W., 69 lks.</p> <p style="text-align: center;">dist. marked T 27 S R 1 E S 32 B T.</p> <p style="text-align: center;">A Fir, 18 ins. diam., bears S.20*E., 43 lks.</p> <p style="text-align: center;">dist. marked S B T.</p> <p>Land, 3rd rate mountainous, rough and rocky.</p> <p>Timber, as usual good, Hemlock, Spruce and Pine.</p>