

10
County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through Tp. 28 S.

CHAINS

on North and S edges, from which

A Cedar, 12 ins. diam., bears S.54*W., 72 lks.

dist. marked T 28 S R | W S 24 B T.

A Hemlock, 12 ins. diam., bears N.20*W., 27 lks.

dist. marked T 28 S R | W S 13 B T.

Land, mountainous.

Soil, stoney and 3rd rate.

Timber, Fir, Pine, Laurel, Hemlock

Undergrowth, Laurel, mountainous or heavily timbered land

or land covered with dense undergrowth. 80.00 chs.

North, bet. secs. 13 and 18 Ascend through heavy
timber and dense undergrowth.

0.18 A Pine, 40 ins. diam., on line I mark with two notches
on N and S sides.

8.55 Dry river, course W

Difference bet. measurement of 40.00 chs. by two sets of
chainmen is 8 lks. position of middle point

By 1st set 40.04

By 2nd set 39.96

the mean of which is

80.00

Set A Basalt stone, 12x10x5 ins. 8 ins. in the ground for
 $\frac{1}{4}$ sec. cor. marked with $\frac{1}{4}$ on W face, from which

A Fir, 12 ins. diam., bears N.41*E., 25 lks.

dist. marked $\frac{1}{4}$ S 18 B T.

A Fir, 8 ins. diam., bears N.49*W., 21 lks.

dist. marked $\frac{1}{4}$ S 13 B T.

41.00 Thence over brush land.

60.00 Steep ascent, hillside bears SE and NW.

Difference bet. measurement of 80.00 chs. by two sets of
chainmen is 16 lks. position of middle point