

County Surveyor's Record, Douglas County, Oregon

North Boundary of Township 29 South, Range 1 East.

CHAINS

Thence over creek bench.

42.00 Leave bench, bears N. and S.; ascend 750 Ft. on NE. slope.

72.25 Spur, slopes SE.; descend 90 ft. on SW. slope.

79.00 Head of Ravine, course S.; ascend 15 ft. on SE. slope, to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 4, 5, 32, and 33, with brass cap marked

T28S | R1E
S32 | S33

S5 | S4
T29S
1921

from which

A Fir, 14 ins. diam., bears N.85*E., 49 lks.
dist. marked T 28 S R 1 E S 33 B T.

A Cedar, 48 ins. diam., bears S.85*E., 29 lks.
dist. marked T 29 S R 1 E S 4 B T.

A Fir, 40 ins. diam., bears S.77*W., 131 lks.
dist. marked T 29 S R 1 E S 5 B T.

A Cedar, 48 ins. diam., bears N.31*W., 84 lks.
dist. marked T 28 S R 1 E S 32 B T.

Land, mountainous.

Soil, stony and shaly clay loam, 2nd and 3d rate.

Timber, Fir, Cedar, and Pine.

Undergrowth, Chinquapin, Laurel, Snowbrush, Hazel.

West, bet. secs. 5 and 32.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 350 ft. on E. slope.

16.80 Spur, slopes SE.; descend 475 ft. on SW. slope to

40.00 Set an iron post, 3 ft. long, 1 ins. diam., 27 ins. in the ground, for 1/4 sec. cor. with brass cap marked

S 32.
1/4 S 5
1921