

Resurvey of the Sixth Standard Parallel South through R 1 E.

CHAINS

Thence

East, on a true line on S. bdy. of Sec. 31.

Asc. broken W. slope; through heavy green timber and dense undergrowth.

- 2.11 The closing Cor. of Tps. 28 S., Rs. 1 E. and 1 W., which is a basalt stone, 10x8x5 ins. above ground, firmly set, marked, CC on N., and 6 grooves on E. and W. faces; from which the original bearing trees

A fir, 12 ins. diam., bears S. 45* E., 100 lks. dist., mkd. T28S R1E S6 BT.

A fir, 18 ins. diam., bears S. 80* W., 24 lks. dist., mkd. T28S R1W S1 BT.

- 8.00 Rocky spur, slopes NW.; asc. NW slope.

- 20.00 Asc. SW. slope.

- 30.00 Rocky spur, slopes NW.; thence over rocky, broken N. slope.

- 38.03 The old Cor. established for standard $\frac{1}{4}$ cor. of sec. 31, bears N. 27 lks. dist.

I destroy all evidence of this cor.

- 40.00 1000 ft. above the standard Tp. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard $\frac{1}{4}$ Sec. cor., with brass cap mkd.

SC
 $\frac{1}{4}$ S31
1927

from which

A fir, 48 ins. diam., bears N. 65* E., 86 lks. dist., mkd. $\frac{1}{4}$ S31 SC BT.

A fir, 30 ins. diam., bears N. 56* W., 76 lks. dist., mkd. $\frac{1}{4}$ S31 SC BT.

Thence over rocky, broken N. slope.

- 62.55 Spring branch, 2 lks. wide, course NW.

- 63.70 Spring branch, 2 lks. wide, course NW.