

County Surveyor's Record, Douglas County, Oregon

Resurvey of the Sixth Standard Parallel South through R. 1 E.

CHAINS

- 66.00 Spring branch, 2 lks. wide, course NW.
- 70.55 Spring branch, 2 lks. wide, course NW.
- 77.80 The old cor. established for standard cor. of secs.
31 and 32, bears N. 45 lks. dist.
I destroy all evidence of this cor.
- 78.50 Spring branch, 2 lks. wide, course NW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for standard cor. of secs. 31 and 32,
with brass cap mkd.

S	C
T27S	R1E
S31	S32
<hr/>	
T28S	R1E
1927	

from which

A hemlock, 10 ins. diam., bears N. $76\frac{1}{2}^*$ E., 45 lks.
dist., mkd. T27S R1E S32 SC BT.

A fir, 24 ins. diam., bears N. 74^* W., 48 lks.
dist., mkd. T27S R1E^E S31 SC BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd and 4th rate.

Timber, fir, pine, cedar, and hemlock.

Undergrowth, vine maple, rhododendron and chinquapin.

East, on S. bdy. of sec. 32.

Over rocky, broken N. slope; through heavy green timber
and dense undergrowth.

- 3.30 Spring branch, 2 lks. wide, course NW.
- 5.35 Branch, 2 lks. wide, course NW.; asc. 885 ft. over
broken W. slope to divide.
- 24.35 Red Butte Trail and telephone line, bear NE. and SW.
- 34.30 Divide between N. and S. Umpqua Rivers, bears N. and S.
Desc. broken SE. slope over cliffs and slide rock.
- 38.17 The old cor. established for standard $\frac{1}{4}$ cor. of sec.
32, bears S. $53\frac{1}{4}^*$ W., 212 lks. dist.
I destroy all evidence of this cor.