

## County Surveyor's Record, Douglas County, Oregon

Resurvey of the Sixth Standard Parallel South through R 1 E.

CHAINS

I destroy all evidence of this cor.

34.00 Spur, slopes SE.; desc. 85 ft. over rolling NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for standard  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\frac{\frac{1}{4}}{4} \begin{matrix} \text{SC} \\ \text{S34} \end{matrix}$$

1927

from which

A fir, 14 ins. diam., bears N. 75\* E., 21 lks.

dist., mkd.  $\frac{1}{4}$  S34 SC BT.

A fir, 30 ins. diam., bears N. 55\* W., 57 lks.

dist., mkd.  $\frac{1}{4}$  S34 SC BT.

Desc. 75 ft. over rolling NE. slope to branch.

43.55 Leave heavy green timber, bears N. and S.; thence across high mountain glade.

46.50 Branch, 1 lk. wide, course S.; asc. gradual SW. slope.

48.50 Old cabin, known as the Perry Duncan Cabin, bears N., 2.00 chs. dist.

49.00 Leave glade; enter heavy green timber, bears N. and S.

52.00 Tiller to Quartz Mountain Trail, bears NW. and SE.

57.25 Quartz Mountain Lookout Trail, bears N. 85\* W. and SE.

59.00 20 ft. above branch; divide between Quartz and Boulder Creeks, bears NW. and SE.; desc. 170 ft. over NE. slope.

70.05 Branch, 2 lks. wide, course N.; thence over broken N. slope.

73.19 The old cor. established for standard cor. of secs. 34 and 35, bears S. 7  $\frac{3}{4}$  \*E., 122 lks. dist.

I destroy all evidence of this cor.

77.45 Spring branch, 2 lks. wide, course N.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for standard cor. of secs. 34 and 35, with brass cap mkd.