

## County Surveyor's Record, Douglas County, Oregon

Resurvey of the Sixth Standard Parallel South through R. 1 E.

CHAINS

S C	
T27S	R1E
S34	S35
-----	
T26S R1E	
1927	

from which

A fir, 20 ins. diam., bears N. 52\* E., 19 lks.  
dist., mkd. T27S R1E S35 SC BT.

A fir, 24 ins. diam., bears N. 60\* W., 13 lks.  
dist., mkd. T27S R1E S34 SC BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 2nd and 3rd rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, vine maple, rhododendron and chinquapin.

East, on S. bdy. of sec. 35.

Over broken N. slope; through heavy green timber and  
dense undergrowth.

3.80 Spur, slopes NE.; desc. 160 ft. over SE. slope.

8.95 Ravine, course NW.; thence over N. slope.

18.50 Spur, slopes N.; desc. NE. slope.

33.53 The old cor. established for standard  $\frac{1}{4}$  cor. of sec.  
35, bears S. 2 $\frac{1}{2}$ \* E., 126 lks. dist.

I destroy all evidence of this cor.

40.00 335 ft. below spur.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground, for standard  $\frac{1}{4}$  Sec. cor., with brass  
cap mkd.

SC	
$\frac{1}{4}$	S35
-----	
1927	

from which

A fir, 24 ins. diam., bears N. 81\* E., 95 lks.  
dist., mkd.  $\frac{1}{4}$  S35 SC BT.

A pine, 12 ins. diam., bears N. 85\* W., 53 lks.  
dist., mkd.  $\frac{1}{4}$  S35 SC BT.

Desc. 485 ft. over NE. slope.