

County Surveyor's Record, Douglas County, Oregon

Resurvey of the Sixth Standard Parallel South through R. 1 E.

CHAINS

- 64.65 Branch, 15 lks. wide, course SE.; asc. SW. slope.
- 72.75 Spring branch, 2 lks. wide, course SW.
- 74.34 The old cor. established for standard cor. of secs.
35 and 36, bears S. $48-3/4^*W.$, 210 lks. dist.
I destroy all evidence of this cor.
- 80.00 85 ft. above branch.
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for standard cor. of secs. 35 and 36,
with brass cap mkd.

| | |
|-------|-----|
| S C | |
| T27S | R1E |
| S35 | S36 |
| ----- | |
| T28S | R1E |
| 1927 | |

from which

- A pine, 16 ins. diam., bears N. $59^* E.$, 59 lks.
dist., mkd. T27S R1E S36 SC BT.
- A fir, 24 ins. diam., bears N. $41^* W.$, 27 lks.
dist., mkd. T27S R1E S35 SC BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, rhododendron and vine maple.

East, on S. bdy. of sec. 36.

Asc. 70 ft. over SW. slope; through heavy green timber
and dense undergrowth.

- 7.65 Spur, slopes S.; desc. 505 ft. over SE. slope.
- 30.45 Branch, 20 lks. wide, course S.; asc. 135 ft. over SW.
slope to spur.
- 32.35 The old cor. established for standard $\frac{1}{4}$ cor. of sec.
36, bears S. $9\frac{1}{2}^* W.$, 140 lks. dist.
I destroy all evidence of this cor.
- 37.00 Flat topped spur, slopes S.; thence over rolling S.
slope.
- 40.00 A fir, 60 ins. diam., for standard $\frac{1}{4}$ sec. cor., I mark
SC $\frac{1}{4}$ S36 on N. side; from which