

County Surveyor's Record, Douglas County, Oregon

Resurvey of the Sixth Standard Parallel South through R. 1 E.

CHAINS

A fir, 30 ins. diam., bears N. 81* E., 104 lks.

dist., mkd. $\frac{1}{4}$ S36 SC BT.

A fir, 5 ins., diam., bears N. 60* W., 21 lks.

dist., mkd. $\frac{1}{4}$ S36 SC BT.

Thence over rolling S. slope.

41.50 Branch, 1 lk. wide, course S. 75* W.; asc. 645 ft. over NW. slope.

60.00 Spur, slopes NW.; asc. 115 ft. over NW. slope to spur.

71.44 The old cor. established for standard Cor. of Tps. 27 S., Rs. 1 and 2 E., bears S. 14-3/4* W., 94 lks. dist.

I destroy all evidence of this cor.

73.80 Spur, slopes SW.; way trail, bears NE. and SW.; thence over broken S. slope.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., \approx ins. in the ground, for standard cor. of Tps. 27 S., Rs. 1 and 2 E., with brass cap mkd.

SC
T27S
R1E R2E
S36 S31
T28S R2E
1927

from which

A fir, 16 ins. diam., bears N. 64* E., 15 lks.

dist., mkd. T27S R2E S31 SC BT.

A Fir, 36 ins. diam., bears N. 68* W., 56 lks.

dist., mkd. T27S R1E S36 SC BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, rhododendron, vine maple and chinquapin.