

Resurvey of the Willamette Meridian through T. 28 S.

CHAINS

Thence

N.0*6'E.

Ascend spur, slopes S.

3.00 Leave spur, slopes S from NE; ascend SW slope.

9.00 Spur, slopes SE; descend 170 ft. over NE slope.

14.35 Ravine, course NE; ascend 10 ft. over SE slope.

16.25 Spur, slopes NE; descend 315 ft. over NE slope.

33.70 Malt Creek, 15 lks. wide, course SE; ascend SW slope.

36.49 Mid point between closing corners determined as

hereinafter set forth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground for $\frac{1}{4}$ cor. of Secs. 30, with brass cap mkd.

|
 $\frac{1}{4}$ S30

1927

from which

A Hemlock, 18 ins. diam., bears N.50*E., 45 lks.
dist., marked $\frac{1}{4}$ S 30 B T.

A Hemlock, 20 ins. diam., bears S.45*E., 58 lks.
dist., marked $\frac{1}{4}$ S 30 B T.

Ascend SW slope.

40.07 90 ft. above Malt Creek.

The cor. established for Secs. 25 and 36, which is a
Basalt stone, 10x8x4 ins. above ground, firmly set,
marked with 5 notches on N and 1 notch on S edges,
from which the original bearing trees

A Fir, 24 ins. diam., bears S.32*W., 79 lks.
dist., marked T 28 S R 1 W S 36 B T.

A Fir, 44 ins. diam., bears N.60*W., 23 lks.
dist., marked T 28 S R 1 W S 25 B T.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd rate.

Timber, Fir, Pine, Cedar and Hemlock.

Undergrowth, Vinemaple, Rhododendron and Salal.