

Resurvey of the Willamette Meridian through T. 28 S.

CHAINS

N. 0° 14' E, on E. bdy. of Sec. 25.

Asc. 10 ft. over SW. slope; through heavy green timber and dense undergrowth.

1.00 Spur, slopes W.; desc. 10 ft. over broken NW. slope.


9.00 Ravine, course W.; asc. 525 ft. over SW. slope.

23.00 Spur, slopes W.; desc. 155 ft. over NW. slope.

30.50 Ravine, course W.; asc. SW. slope.

36.39 Point of intersection of line bet. secs. 19 and 30, T 28 S., R. 1 E., determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 19 and 30, with brass cap mkd.



from which

A fir, 10 ins. diam., bears N. 74° E., 48 lks. dist., mkd. T28S R1E S19 CC BT.

A fir, 36 ins. diam., bears S. 20° E., 47 lks. dist., mkd. T28 S R1E S30 CC BT.

Thence over W. slope.

40.11 The 1/4 cor. established for secs. 25 and 30, which is a basalt stone, 12x8x5 ins., above ground, firmly set, mkd. 1/4 on W. face; from which the original bearing trees

A fir, 12 ins. diam., bears N. 70° E., 10 lks. dist., mkd. 1/4 S30 BT.

A fir, 24 ins. diam., bears West, 6 lks. dist., mkd. 1/4 S25 BT.

I now change this corner to refer to Sec. 25 only.

I destroy the markings on bearing tree in sec. 30 and take new bearing tree as follows:

A fir, 34 ins. diam., bears N. 8 3/4° W., 28 lks. dist., mkd. 1/4 S25 BT.