

Resurvey of the Willamette Meridian through T 28 S.

CHAINS

N.0°8'E., on E bdy. of Sec. 24.

Over W slope; through heavy green timber and dense undergrowth.

2.20 Ravine, course SW; ascend 365 ft. over SE slope.

10.60 Spur, slopes S.70°W; descend 155 ft. over NW slope.

14.10 Ravine, course NW; asc. 185 ft. over SW slope to spur.

25.85 Big Squaw Way Trail, bears NW and SE.

28.80 Spur, slopes S.30°E; descend 225 ft. over NE slope to head of ravine.

36.48 Point of intersection of line bet. Secs. 18 and 19, T 28 S., R. 1 E., determined as hereinafter set forth. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of Secs. 18 and 19, with brass cap marked

	T28S	
T28S	S18	CC
R1W	S19	
S24	R1E	
	1927	

from which

A Fir, 22 ins. diam., bears N.73°E., 9 lks. dist., marked T 28 S R 1 E S 18 C C B T.

A Fir, 22 ins. diam., bears S.45°E., 17 lks. dist., marked T 28 S R 1 E S 19 C C B T.

38.10 Head of ravine, course E; ascend 65 ft. over SE slope.

39.85 The  $\frac{1}{4}$  cor. established for Secs. 19 and 24, which is a Basalt stone, 10x5x4 ins., above ground, firmly set, marked  $\frac{1}{4}$  on W face, from which the original bearing trees

A Fir, 18 ins. diam., bears S.75°E., 17 lks. dist., marked  $\frac{1}{4}$  S 19 B T.

A Fir, 16 ins. diam., bears S.89°W., 33 lks. dist., marked  $\frac{1}{4}$  S 24 B T.

I now change this cor. to refer to Sec. 24 only.

I destroy the markings on bearing tree marked for Sec. 19 and take new bearing tree as follows: