

Resurvey of the Willamette Meridian through T. 28 S.

CHAINS

N. 0° 10' W., on E. bdy. of sec. 12.

Desc. 405 ft. over broken NE. slope; through heavy green timber and dense undergrowth.

11.35 Branch, 2 lks. wide, course E.; asc. 145 ft. over SE. slope.

16.65 Spur, slopes S. 60° E.; desc. 65 ft. over NE. slope.

21.75 Branch, 1 lk. wide, course SE.; asc. 225 ft. over SW. slope.

26.75 Spur, slopes SE.; desc. 155 ft. over NE. slope to branch.

37.25 Point of intersection of line bet. secs. 6 and 7, T. 28 S., R. 1 E., determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 6 and 7, with brass cap mkd.

	T28S	
T28S	S6	CC
R1W	S7	
S12	R1E	
	1928	

from which

A fir, 16 ins. diam., bears N. 32° E., 12 lks. dist., mkd. T28S R1E S6 CC BT.

A fir, 14 ins. diam., bears S. 38° E., 30 lks. dist., mkd. T28S R1E S7 CC BT.

38.30 Branch, 1 lk. wide, course SE.; asc. 65 ft. over SW. slope.

40.33 The 1/4 cor. established for secs. 7 and 12, which is a basalt stone, 8x5x4 ins., above ground, firmly set, mkd. 1/4 on W. face; from which the original bearing trees

A fir, 24 ins. diam., bears S. 12° E., 26 lks. dist.; mkd. 1/4 S7 BT.

A fir, 18 ins. diam., bears S. 44° W., 55 lks. dist., mkd. 1/4 S12 BT.

I now change this cor. to refer to sec. 12 only.