

## County Surveyor's Record, Douglas County, Oregon

Resurvey of the Willamette Meridian through T. 28 S.

CHAINS

I destroy the markings on bearing tree marked for sec. 7 and take new bearing tree as follows:

A fir, 16 ins. diam., bears N. 8\*W., 51 lks. dist., mkd.  $\frac{1}{4}$  S12 BT.

Thence

N. 1\* 6' E.

Asc. 535 ft. over SW. slope.

18.10 Divide between N. and S. Umpqua Rivers, bears E. and W. Red Butte Trail and telephone line, bear E. and W. Descend 820 ft. over broken N. slope to sec. cor.

35.50 Branch, 2 lks. wide, course N. 25\* W.

36.93 40.00 chs. northing from the closing corner of secs. 6 and 7, T. 28 S., R. 1 E., determined as hereinafter set forth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 6, with brass cap mkd.

$\frac{1}{4}$ S6

1928

from which

A hemlock, 20 ins. diam., bears N. 9\* E., 42 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

A hemlock, 12 ins. diam., bears S. 65 $\frac{1}{2}$ \* E., 12 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

39.53 The cor. established for secs. 1 and 12, which is a basalt stone, 10x6x4 ins. above ground, firmly set, mkd. with 1 notch on N. and 5 notches on S. edge; from which the original bearing trees.

A hemlock, 16 ins. diam., bears S. 30\* W., 8 lks. dist., mkd. T28S R1W S12 BT.

A hemlock, 14 ins. diam., bears N. 50\* W., 25 lks. dist., mkd. T28S R1W S1 BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd rate.