

County Surveyor's Record, Douglas County, Oregon

Resurvey of the Willamette Meridian through T. 28 S.

CHAINS

Timber, fir, hemlock and cedar.

Undergrowth, vinemaple, rhododendron, chinquapin, manzanita and madrona.

N. 0° 35' E., on E. bdy. of sec. 1.

Descend broken N. slope; through heavy green timber and dense undergrowth.

3.10 Same branch as noted at 35.50 chs. on N. $\frac{1}{2}$ mile of E. bdy. of sec. 12, 2 lks. wide, course N. 30° E.

10.30 215 ft. below the sec. cor.

Same branch, 3 lks. wide, course NW.

Ascend 30 ft. over SW. slope.

12.30 Point of spur, slopes W.

Descend 190 ft. over N. slope.

20.15 Branch, 3 lks. wide, course N. 60° W.

Ascend 75 ft. over SW. slope.

30.42 The closing corner of Ts. 28 S., Rs. 1 E. and 1 W., which is a basalt stone, 10x8x5 ins., above ground, firmly set, marked CC on N. and 6 grooves on E. and W. faces.

From which the original bearing trees.

A fir, 12 ins. diam., bears S. 45° E., 100 lks. dist., mkd. T28S R1E S 6 BT.

A fir, 18 ins. diam., bears S. 80° W., 24 lks. dist., mkd. T28S R1W S1 BT.

This closing township corner is 95 ft. above the standard corner of Tps. 27 S., Rs. 1 E. and 1 W.

From this closing township cor. the standard corner of Tps. 27 S., Rs. 1 E. and 1 W. bears West, 2.11 chs. dist.