

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of T. 28 S., R. 1 E.

## CHAINS

68.40 Branch, 15 lks. wide, course E.; asc. SE. slope.

73.00 Spring branch, 1 lk. wide, course SE.

80.00 Spur, slopes SE., 310 ft. above branch.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

T28S R1E	
S2	S1
S11	S12
1927	

from which

A fir, 16 ins. diam., bears N. 55 3/4\* E., 17 lks. dist., mkd. T28S R1E S1 BT.

A fir, 20 ins. diam., bears S. 41 1/2\* E., 8 lks. dist., mkd. T28S R1E S12 BT.

A pine, 48 ins. diam., bears S. 61 1/2\* W., 39 lks. dist., mkd. T28S R1E S11 BT.

A pine, 50 ins. diam., bears N. 22\* W., 45 lks. dist., mkd. T28S R1E S2 BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd rate.

Timber, pine, fir, cedar and hemlock.

Undergrowth, rhododendron, vine maple and chinquapin.

---

N. 89\* 52' E., on a random line bet. secs. 1 and 12.

40.00 Set temp. 1/4 sec. cor.

80.44 Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs. 1, 6, 7 and 12, previously described in field notes of T. 28 S., R. 2 E., this group.

Thence

S. 89\* 55' W., on a true line bet. secs. 1 and 12.

Desc. 20 ft. over SW. slope; through heavy green timber and dense undergrowth.

8.75 Spur, slopes SW.; desc. 950 ft. over NW. slope.

40.22 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.