

Subdivision of T. 28 S., R. 1 E.

CHAINS

A hemlock, 9 ins. diam., bears N. 42* W., 7 lks. dist., mkd. $\frac{1}{2}$ S2 BT.

Desc. 50 ft. over rolling NE. slope.

50.75 Branch, 25 lks. wide, course S. 20* E.; asc. 390 ft. over SW. slope.

73.77 Intersect the Sixth Standard Parallel South, 1.67 chs., West from the standard cor. of secs. 35 and 36, heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.

T27S	R1E
S35	
<hr style="width: 50%; margin: 0 auto;"/>	
S2	S1
T28S	R1E
C	C
1927	

from which

A pine, 36 ins. diam., bears S. 65 $\frac{1}{4}$ * E., 77 lks. dist., mkd. T28S R1E S1 CC BT.

A pine, 10 ins. diam., bears S. 81 $\frac{1}{2}$ * W., 155 lks. dist., mkd. T28S R1E S2 CC BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 2nd and 3rd rate.

Timber, pine, fir and cedar.

Undergrowth, rhododendron, vine maple and chinquapin.

From the cor. of secs. 2, 3, 34 and 35, on S. bdy. of Tp., previously described in field notes of T. 29 S., R. 1 E., this group.

N. 0* 2' W., bet. secs. 34 and 35.

Over rolling bench; through heavy green timber and dense undergrowth.

4.00 Branch, 1 lk. wide, course E.; asc. 215 ft. over SE. slope.

20.00 Spur, slopes E.; desc. 30 ft. over NE. slope.

23.14 Branch, 5 lks. wide, course S. 20* E.; asc. 280 ft. over SW. slope.