


County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 1 E.

CHAINS

- 10.80 Branch, 2 lks. wide, course N. 60* E.; asc. 20 ft. over rolling SE. slope.
- 28.00 Spur, slopes N. 60* E.; desc. 160 ft. over NE. slope.
- 36.75 Branch, 4 lks. wide, course E.; asc. 10 ft. over SE. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.




from which

- A fir, 12 ins. diam., bears N. 64* E., 33 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
- A pine, 48 ins. diam., bears N. 21* W., 11 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

Asc. 40 ft. over SE. slope.

- 44.00 Spur, slopes E.; desc. 80 ft. over NE. slope.
- 47.90 Branch, 2 lks. wide, course E.; asc. 150 ft. over SE. slope.
- 53.00 Spur, slopes E.; desc. 280 ft. over NE. slope.
- 64.40 Branch, 4 lks. wide, course SE.; asc. 440 ft. over SW. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.



from which

- A fir, 12 ins. diam., bears N. 64* E., 15 lks. dist., mkd. T28S R1E S23 BT.
- A fir, 12 ins. diam., bears S. 75* E., 55 lks. dist., mkd. T28S R1E S26 BT.
- A fir, 28 ins. diam., bears S. 20* W., 54 lks. dist., mkd. T28S R1E S27 BT.