

Subdivision of T. 28 S., R. 1 E.

CHAINS

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for corner of secs. 14, 15, 22 and 23, with brass cap marked

T28S R1E	
S15	S14
S22	S23
1927	

from which

A fir, 24 ins. diam., bears N.65 $\frac{1}{2}$ \*E., 70 lks. dist., mkd. T28S R1E S14 BT.

A fir, 10 ins. diam., bears S.61 $\frac{1}{2}$ \*E., 54 lks. dist., mkd. T28S R1E S23 BT.

A fir, 10 ins. diam., bears S.60 $\frac{1}{2}$ \*W., 43 lks. dist., mkd. T28S R1E S22 BT.

A fir, 18 ins. diam., bears N.42 $\frac{1}{2}$ \*W., 37 lks. dist., mkd. T28S R1E S15 BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; third rate.

Timber, fir, cedar, pine, madrona and chinquapin.

Undergrowth, vine maple, rhododendron and chinquapin.

---

N.89\*54'E., on a random line between sections 14 and 23.

40.00 Set temp.  $\frac{1}{4}$  sec. corner.

80.02 Intersect N. and S. line 7 lks. S. of the corner of secs. 13, 14, 23 and 24.

Thence

South, 89\* 51' W., on a true line between sections 14