

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 1 E.

CHAINS

with brass cap, mkd.

T28S	R1E
S10	S11
<hr/>	
S15	S14
1927	

from which

A fir, 14 ins. diam., bears N. 76* E., 27 lks. dist., mkd. T28S R1E S11 BT.

A fir, 16 ins. diam., bears S. 88* E., 9 lks. dist., mkd. T28S R1E S14 BT.

A pine, 12 ins. diam., bears S. 80*W., 34 lks. dist., mkd. T28S R1E S15 BT.

A cedar, 20 ins. diam., bears N. 65* W., 5 lks. dist., mkd. T28S R1E S10 BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, vine maple, rhododendron, chinquapin and hazel.

N. 89* 51' E., on a random line bet. secs. 11 and 14.

40.00 Set temp. 1/4 sec. cor.

79.70 Intersect N. and S. line, 21 lks. N. of the cor. of secs. 11, 12, 13 and 14.

Thence

West, on a true line bet. secs. 11 and 14.

Asc. 400 ft. over NE. slope; through heavy green timber and dense undergrowth.

31.00 Spur, slopes NE.; asc. 145 ft. over NE. slope.

39.85 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap, mkd.

S11

1/4 _____

S14
1927

from which