

Subdivision of T 28 S., R. 1 E.

CHAINS

the ground, for witness cor. to $\frac{1}{4}$ sec. cor.,
with brass cap, mkd.

W C
↑
S3 | S2
1927

from which

A fir, 20 ins. diam., bears S. 16* E., 30 lks.
dist., mkd. WC $\frac{1}{4}$ S2 BT.

A hemlock, 12 ins. diam., bears S. 80* W., 13 lks.
dist., mkd. WC $\frac{1}{4}$ S3 BT.

37.20 Leave heavy timber, bears E. and W.; thence over bare
rock slide

39.15 Head of ravine, course SW.; 30 ft. below spur.
Asc. SW. slope.

40.00 Point for $\frac{1}{4}$ sec. cor. falls on insecure ground.

43.20 Leave rock slide; thence over small cliffs and slide
rock.

54.10 Spur, slopes NW.; 495 ft. above head of ravine.
Quartz Mountain Look Out Trail, bears NW. and SE.
Enter heavy timber, bears NW. and SE.
Desc. NE. slope.

66.60 Spur, slopes NE.; desc. NW. slope.

73.95 420 ft. below the spur at 54.10 chs.

Intersect the Sixth Standard Parallel South, 1.47 chs.,
West. from the standard cor. of secs. 34 and 35,
heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for closing cor. to secs. 2 and 3,
with brass cap, mkd.

T27S R1E
S34

S3 | S2
T28S | R1E
C | C
1927

from which