

Subdivision of T. 28 S., R. 1 E.

CHAINS

from which


A Pine, 12 ins. diam., bears N.42°E., 87 lks. dist., marked 1/4 S 3 B T.

A Fir, 22 ins. diam., bears S.28 1/2°E., 20 lks. dist., marked 1/4 S 10 B T.

- 44.90 Descend 190 ft. over NW slope.
- Branch, 5 lks. wide, course S.60°W., ascend 140 ft. over SW slope.
- 57.30 Spur, slopes S; descend 115 ft. over SW slope.
- 62.10 Ravine, course S.30°W., ascend 65 ft. over SE slope.
- 65.40 Spur, slopes S; descend 285 ft. over SW slope.
- 77.40 Ravine, course S; ascend 45 ft. over SE slope to Sec. cor.
- 78.75 Top of cliff, 40 ft. high, facing E; bears N and S.
- 80.42 The cor. of Secs. 3, 4, 9 and 10.

Land, mountainous.
Soil, loose, coarse, rocky loam; 3rd rate.
Timber, Fir, Pine and Cedar.
Undergrowth, Vinemaple, Rhododendron and Chinquapin.

- N.0°2°W., on a true line bet. Secs. 3 and 4.
- Ascend 200 ft. over SE slope; through heavy green timber and dense undergrowth.
- 7.40 Spur, slopes W; descend 40 ft. over NW slope.
- 20.40 Branch, 15 lks. wide, course S.60°W; ascend 55 ft. over SE slope.
- 22.80 Point of spur, slopes E; thence over E slope.
- 24.80 Branch, 8 lks. wide, course E; thence over E slope.
- 26.00 Branch, 6 lks. wide, course SE from N.
- 27.30 Leave branch, course S from NW; ascend SW slope.
- 30.55 Spur, slopes W; 110 ft. above point noted at 22.80 chs.
- Descend 15 ft. over NW slope.
- 32.50 Branch, 1 lk. wide, course S.75°W; ascend 60 ft. over SE slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground; for 1/4 Sec. cor., with brass cap marked



from which

A Fir, 14 ins. diam., bears S.88°E., 57 lks. dist., marked 1/4 S 3 B T.

A Fir, 26 ins. diam., bears N.74°W., 24 lks. dist., marked 1/4 S 4 B T.

Ascend 20 ft. over SE slope.

- 42.00 Point of spur, slopes SW; descend 20 ft. over NW slope.
- 42.50 Branch, 2 lks. wide, course S.20°W; ascend 900 ft. over SE slope.
- 73.83 Intersect the Sixth Standard Parallel South, 175 lks. West from the Standard corner of Secs. 33 and 34, hereto-