

Subdivisions of T. 28 S., R. 1 E.

CHAINS

N.0\*3'W., between Sections 28 and 29.  
Asc. 250 ft. over SE. slope, through heavy green timber and dense undergrowth.


12.40 Spur, slopes E., desc. 65 ft. over NE. slope.

16.75 Branch, 1 lk. wide, C. E., asc. 275 ft. over SE. slope to divide.

28.35 Way Trail, bears NE. and SW.

28.60 Divide bet. Rock and Boulder Creeks, bears NE. and SW.  
Desc. 255 ft. over spur, slopes N.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap, mkd:



from which


A Fir, 5 ins. diam., bears S.50\*E., 6 lks. dist.,  
mkd.:  $\frac{1}{4}$  S28 BT.

A Fir, 24 ins. diam., bears S.27\*W., 20 lks. dist.,  
mkd.:  $\frac{1}{4}$  S29 BT.

Desc. 615 ft. over spur; slopes N.

56.40 Branch, 5 lks. wide, C. W., asc. 950 ft. over SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of Secs. 20, 21, 28 and 29, with brass cap, mkd.:



from which

A Fir, 12 ins. diam., bears N.63\*E., 37 lks. dist.,  
mkd.: T28S R1E S21 BT.

A Fir, 12 ins. diam., bears S.77\*E., 42 lks. dist.,  
mkd.: T28S R1E S28 BT.

A Fir, 35 ins. diam., bears S.61\*W., 67 lks. dist.,  
mkd.: T28S R1E S29 BT.