

Subdivision of T. 28 S., R. 1 E.

CHAINS

From the cor. of secs. 7, 8, 17 and 18, heretofore described.

N.0* 4' W., bet secs. 7 and 8.

Asc. 35 ft. over Eth. slope; through heavy green timber and dense undergrowth.


2.00 Spur, slopes SW.; desc. 60 ft. over NW. slope.

6.00 Head of ravine, course SW.; asc. 170 ft. over SW. slope.

11.00 Spur, slopes W.; desc. 375 ft. over NW. slope.

31.70 Ravine, course SW.; asc. 340 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap, mkd.



from which

A fir, 12 ins. diam., bears S. $62\frac{1}{2}^*$ E., 18 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A cedar, 24 ins. diam., bears S. $10\frac{3}{4}^*$ W., 67 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

Asc. 260 ft. over SE. slope.

48.00 Spur, slopes S. 75^* W.; desc. 65 ft. over NW. slope.

55.00 Ravine, course W.; asc. 245 ft. over SW. slope.

72.00 Spur, slopes W.; foot of impassable cliff, 300 ft.

high, facing S., bears E. and W. To pass the cliff, I offset 2.00 chs. W., then N. 0^* 4' W. on the offset line.

Desc. NW. slope and continue offset line to 75.00 chs.; then E. 2.00 chs., to true line.

78.15 Ravine, course SW.; 95 ft. below point at foot of cliff at 72.00 chs.; asc. 55 ft. over SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, with brass cap, mkd.

