

Subdivision of T. 28 S., R. 1 E.

CHAINS

and dense undergrowth

8.60 Spur, slopes SW.; asc. 725 ft. over SW. slope.

31.10 Divide between N. and S. Umpqua Rivers, bears NE. and SW.; desc. 85 ft. over rolling NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, for  $\frac{1}{2}$  sec. cor., with brass cap, mkd.

$$\begin{array}{c} \frac{1}{2} \\ | \\ S6 | S5 \\ | \\ 1928 \end{array}$$

from which

A fir, 40 ins. diam., bears East, 43 lks.

dist., mkd.  $\frac{1}{4}$  S5 BT.

A fir, 14 ins. diam., bears S. 84\* W., 65 lks.

dist., mkd.  $\frac{1}{4}$  S6 BT.

Desc. broken N. slope, 645 ft. to closing cor.

46.00 Red Butte Trail and telephone line, bears E. and W.

73.47 Intersect the Sixth Standard Parallel South, 1.81 chs., West from the standard cor. of secs. 31 and 32, heretofore described.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap, mkd.

$$\begin{array}{c} T27S R1E \\ \hline S31 \\ \hline S6 | S5 \\ T28S | R1E \\ C | C \\ 1928 \end{array}$$

from which

A hemlock, 14 ins. diam., bears S. 57 3/4\* E., 68 lks

dist., mkd. T28S R1E S5 CC BT.

A hemlock, 12 ins. diam., bears S. 11 1/2\* W., 50 lks.

dist., mkd. T28S R1E S6 CC BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, vine maple, rhododendron and chinquapin.