

## County Surveyor's Record, Douglas County, Oregon

East and West Boundaries and Subdivisions  
of T. 28 S. R. 2 E., and Resurvey of the Sixth Stan. Par.  
South through R 2 E., as surveyed by Lincoln Wilkes, U.S.C.E.  
under special instructions, dated December 21, 1920.

## CHAINS

Resurvey of the Sixth Stan. Par. South through R 2 E.

Having determined by retracement that this line is  
out of limits both in alignment and measurement,  
I proceed with an independent resurvey of same.

From the standard cor. of Tps. 27 S., Rs. 1 and 2 E.,  
East, on a true line, on S. bdy. of sec. 31.

Desc. 80 ft. over SW. slope; through heavy green timber  
and dense undergrowth.

- 8.35 Ravine, course SW.; asc. 445 ft. over SW. slope.  
22.60 Spur, slopes S.; desc. 95 ft. over E. slope to branch.  
24.90 Five Lakes Trail, bears N. and S.  
30.79 The old standard  $\frac{1}{4}$  sec. cor., bears S., 86 lks. dist.  
I destroy all evidence of this cor.  
34.70 Branch, 4 lks. wide, course SE.; asc. 45 ft. over SW.  
slope.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for standard  $\frac{1}{4}$  sec. cor., with brass cap  
mkd:

SC  
 $\frac{1}{4}$  S31

1927

from which:

A fir, 30 ins. diam., bears N.38\*E., 59 lks..  
dist., mkd.  $\frac{1}{4}$  S 31 S C B T

A fir, 30 ins. diam., bears N.53 $\frac{1}{2}$ \*W., 41 lks..  
dist., mkd.  $\frac{1}{4}$  S 31 S C B T

Asc. 115 ft. over SW. slope.

- 57.70 Spur, slopes S.; desc. 160 ft. over SW. slope to  
standard sec. cor.  
71.15 The old cor. established for standard cor. of secs.  
31 and 32, bears S., 1.07 chs. dist.  
I destroy all evidence of this cor.