

County Surveyor's Record, Douglas County, Oregon

Resurvey of the Sixth Standard Parallel South through R. 2 E.

| | | | | | | | |
|--------|--|---|---|------|-----|-----|-----|
| CHAINS | <p>Desc. 50 ft. over SE. slope.</p> <p>46.10 Ravine, course S.; asc. 245 ft. over SW. slope.</p> <p>70.00 Spur, slopes S.; desc. 75 feet over E. slope to standard sec. cor.</p> <p>71.28 The old cor. established for standard cor. of secs. 32 and 33, bears N., 52 lks. dist. I destroy all evidence of this cor.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for standard cor. of secs. 32 and 33, with brass cap mkd.</p> | | | | | | |
| | <table border="1"> <tr><td>S</td><td>C</td></tr> <tr><td>T27S</td><td>R2E</td></tr> <tr><td>S32</td><td>S33</td></tr> </table> | S | C | T27S | R2E | S32 | S33 |
| S | C | | | | | | |
| T27S | R2E | | | | | | |
| S32 | S33 | | | | | | |
| | <p>1927 from which:</p> <p>A cedar, 38 ins. diam., bears N.32*E., 73 lks. dist., mkd. T 27 S R 2 E S 33 S C B T</p> <p>A fir, 30 ins. diam., bears N.32*W., 49 lks. dist., mkd. T 27 S R 2 E S 32 S C B T</p> | | | | | | |
| | <p>Land, mountainous.</p> <p>Soil, loose, coarse, rocky loam; 3rd. rate.</p> <p>Timber, fir, cedar and pine.</p> <p>Undergrowth, vine maple and rhododendron.</p> | | | | | | |
| | <p>East, on S. bdy. of sec. 33.</p> <p>Desc. 415 ft. over E. slope; through heavy green timber and dense undergrowth.</p> | | | | | | |
| 25.30 | Branch, 5 lks. wide, course S.; asc. 215 ft. over W. slope to spur. | | | | | | |
| 31.30 | The old standard $\frac{1}{4}$ sec. cor., bears N.27 lks. dist. I destroy all evidence of this cor. | | | | | | |
| 36.15 | Spur, slopes S.; desc. 40 ft. over SE. slope. | | | | | | |
| 40.00 | Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd. | | | | | | |

| |
|-------------------|
| SC |
| $\frac{1}{4}$ S33 |

1927