

Resurvey of the Sixth Standard Parallel South through  
R. 2 E.

CHAINS							
	<p>from which</p> <p>A fir, 42 ins. diam., bears N.28*E., 27 lks. dist. mkd. <math>\frac{1}{4}</math> S 33 S C B T.</p> <p>A cedar, 10 ins. diam., bears N.32*W., 47 lks. dist. mkd. <math>\frac{1}{4}</math> S 33 S C B T.</p> <p>Desc. 25 ft. over SE. slope.</p>						
42.50	<p>Branch, 2 lks. wide, course S.; asc. 45 ft. over SW., slope.</p>						
48.00	<p>Spur, slopes S.; desc. 30 ft. over SE. slope.</p>						
54.10	<p>Branch, 3 lks. wide, course S.; thence over S. slope.</p>						
55.35	<p>Spring branch, 1 lk. wide, course SW.; asc. 15 ft. over SW. slope.</p>						
64.00	<p>Spur, slopes S.; desc. 130 ft. over E. slope to standard sec. cor.</p>						
71.67	<p>The old cor. established for standard cor. of secs. 33 and 34, bears N., 50 lks. dist.</p> <p>I destroy all evidence of this cor.</p>						
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for standard cor. of secs. 33 and 34, with brass cap mkd.</p>						
	<table border="1"> <tr> <td>S</td> <td>C</td> </tr> <tr> <td>T27S</td> <td>R2E</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> </table> <p>1927</p>	S	C	T27S	R2E	S33	S34
S	C						
T27S	R2E						
S33	S34						
	<p style="text-align: right;">from which</p> <p>A fir, 40 ins. diam., bears N.50*E., 16 lks. dist. mkd. T 27 S R 2 E S 34 S C B T</p> <p>A fir, 40 ins. diam., bears N.32<math>\frac{1}{2}</math>*W., 73 lks. dist., mkd. T 27 S R 2 E S 33 S C B T</p> <p>Land, mountainous.</p> <p>Soil, loose, coarse, rocky loam; 3rd. rate.</p> <p>Timber, fir, cedar and pine.</p> <p>Undergrowth, vine maple and rhododendron.</p>						