

Resurvey of the Sixth Standard Parallel South through R 2 E

CHAINS	
	East, on S. bdy. of sec. 34.
	Desc. 610 ft. over E. slope; through heavy green timber and dense undergrowth.
20.00	Branch, 15 lks. wide, course S.; asc. 495 ft. over W. slope to the standard $\frac{1}{4}$ sec. cor.
31.27	The old standard $\frac{1}{4}$ sec. cor., bears N., 72 lks. dist. I destroy all evidence of this cor.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \text{SC} \\ \hline \frac{1}{4} \text{ S34} \\ 1927 \end{array}$
	from which
	A fir, 36 ins. diam., bears N.59 $\frac{1}{2}$ *E., 17 lks. dist. mkd. $\frac{1}{4}$ S 34 S C B T
	A cedar, 24 ins. diam., bears N.24 $\frac{1}{2}$ *W., 17 lks. dist., mkd. $\frac{1}{4}$ S 34 S C B T
	Asc. 945 ft. over W. slope.
68.00	Spur, slopes S.; desc. 445 ft. over E. slope to the standard sec. cor.
71.27	Find no evidence of the old standard cor. established for sec. 34 and 35.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins in the ground, for standard cor. of secs. 34 and 35, with brass cap mkd.
	$\begin{array}{c} \text{S C} \\ \text{T27 S} \mid \text{R2E} \\ \hline \text{S34} \mid \text{S35} \end{array}$
	1927
	from which
	A fir, 30 ins. diam., bears N.81*E., 138 lks. dist. mkd. T 27 S R 2 E S 35 S C B T
	A fir, 6 ins. diam., bears N.36*W., 8 lks. dist., mkd. T 27 S R 2 E S 34 S C B T