

County Surveyor's Record, Douglas County, Oregon

Resurvey of the Sixth Standard Parallel South through R. 2 E.

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir. 18 ins. diam., bears N.40$\frac{1}{2}$*E., 126 lks. dist., mkd. T 27 S R 2 E S 36 S C B T</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N.80*W., 90 lks. dist., mkd. T 27 S R 2 E S 35 S C B T</p> <p>Land, mountainous.</p> <p>Soil, loose, coarse, rocky loam; 3rd. rate.</p> <p>Timber, fir, pine and cedar.</p> <p>Undergrowth, chinquapin and hazel.</p>
	<p>East, on S. bdy. of sec. 36.</p> <p>Desc. 85 ft. over NE. slope; through heavy green timber and dense undergrowth.</p>
2.90	Branch, 4 lks. wide, course SE., asc. 35 ft. over SW. slope.
8.00	Spur, slopes S., desc. 100 ft. over SE. slope.
15.60	Head of ravine, course S., asc. 60 ft. over SW. slope.
23.00	Spur, slopes SE., desc. 20 ft. over broken SE. slope to the standard $\frac{1}{4}$ sec. cor.
27.39	The old standard $\frac{1}{4}$ sec. cor., bears N., 192 lks. dist. I destroy all evidence of this cor.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<p>SC</p> <p><u>$\frac{1}{4}$ S 36</u></p> <p>1927</p>
	<p>from which:</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N.37*E., 56 lks. dist. mkd. $\frac{1}{4}$ S 36 S C B T</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N.50$\frac{1}{8}$*W., 20 lks. dist. mkd. $\frac{1}{4}$ S 36 S C B T</p> <p>Desc. 290 ft. over broken SE. slope.</p>
55.30	Branch, 15 lks. wide, course S., thence over S. slope.
56.80	Branch, 20 lks. wide, course SW., asc. 350 ft. over