

Subdivision of T. 28 S., R. 2 E.

CHAINS


North 0°1'W., on a true line bet. secs. 1 and 2.
Asc. 35 ft. over SE. slope; through heavy green
timber and dense undergrowth.

1.85 Spur, slopes SE., desc. 90 ft. over NE. slope.

13.50 Branch, 1 lk. wide, course E., asc. 630 ft. over SE.
slope.

28.50 Spur, slopes SE., desc. 35 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which:

A fir, 30 ins. diam., bears N.38°E., 32 lks.
dist., mkd. $\frac{1}{4}$ S 1 B T


A fir, 30 ins. diam., bears N.50°W., 38 lks.
dist., mkd $\frac{1}{4}$ S 2 B T

Desc. 285 ft. over broken NE. slope.

74.30 Intersect the Sixth Standard Parallel South, 7.35 chs.,
West from the standard cor. of secs. 35 and 36,
heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for closing cor. of secs. 1 and 2,
with brass cap mkd.



from which:

A pine, 12 ins. diam., bears S.41°E., 27 lks.
dist. mkd. T 28 S R 2 E S 1 C C B T

A pine. 16 ins. diam., bears S.59°W., 10 lks.
dist. mkd. T 28 S R 2 E S 2 C C B T

Land, mountainous.