

County Surveyor's Record, Douglas County, Oregon

54

Subdivision of T. 28 S., R. 2 E.

CHAINS									
	<p>A fir, 12 ins. diam., bears S.41*E., 23 lks. dist. mkd. ¼ S 23 B T</p> <p>A cedar, 24 ins. diam., bears N.64*W., 34 lks. dist., mkd. ¼ S 22 B T</p> <p>Asc. 85 ft. over SE. slope.</p>								
45.00	Spur, slopes W., desc. spur, slopes N.								
55.60	Leave spur, slopes NW., desc. NE. slope.								
71.50	715 ft. below spur at 45.00 chs.; ravine, course E. Asc. 65 ft. over SE. slope.								
74.30	Spur, slopes E., desc. 40 ft. over NE. slope.								
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 14,15,22 and 23, with brass cap mkd.								
	<table border="1"> <tr> <td>T28S</td> <td>R2E</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2">1927</td> </tr> </table>	T28S	R2E	S15	S14	S22	S23	1927	
T28S	R2E								
S15	S14								
S22	S23								
1927									
	<p>from which:</p> <p>A fir, 30 ins. diam., bears N.61*E., 27 lks. dist., mkd. T 28 S R 2 E S 14 B T</p> <p>A fir, 48 ins. diam., bears S.59*E., 86 lks. dist., mkd. T 28 S R 2 E S 23 B T</p> <p>A pine, 5 ins. diam., bears S.34*W., 36 lks. dist., mkd. T 28 S R 2 E S 22 B T</p> <p>A fir, 28 ins. diam., bears N.20*W., 38 lks. dist., mkd. T 28 S R 2 E S 15 B T</p> <p>Land, mountainous. Soil, loose, coarse, rocky loam; 3rd. rate. Timber, fir, pine and cedar Undergrowth, vine maple, rhododendron and laurel.</p>								
	<p>East, on a random line bet. secs. 14 and 23.</p>								
40.00	Set temp. ¼ sec. cor.								
80.02	Intersect N. and S. line, 18 lks. S. of the cor. of secs. 13,14, 23 and 24.								