

Subdivision of T. 28 S., R. 2 E.

CHAINS

A fir, 12 ins. diam., bears N.7\*E., 89 lks.  
dist., mkd.  $\frac{1}{4}$  S 2 B T

A pine, 8 ins. diam., bears N.30\*W., 129 lks.  
dist., mkd.  $\frac{1}{4}$  S 3 B T

Asc. 250 ft. over SE. slope.

73.70 Intersect the Sixth Standard Parallel South, 7.17 chs.,  
West from the standard cor. of secs. 34 and 35,  
heretofore described.

At point of intersection,

Set a basalt stone, 25 x 10 x 8 ins., 18 ins. in the  
ground, for closing cor. of secs. 2 and 3, marked  
CC and 6 grooves on S. face and 2 grooves on E. and  
4 grooves on W. face; from which:

A fir, 12 ins. diam., bears S.86\*E., 250 lks.  
dist., mkd. T 28 S R 2 E S 2 CC B T

A fir, 30 ins. diam., bears S.14 $\frac{1}{2}$ \*W., 230 lks.  
dist., mkd. T 28 S R 2 E S 3 CC B T

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd. rate.

Timber, fir, pine and cedar.

Undergrowth, chinquapin and hazel.

From the cor. of secs. 3, 4, 33 and 34, and S. bdy. of  
Tp., previously described in field notes of T. 29 S.,  
R.2 E., this group.

North 0\*2'W., bet. secs. 33 and 34.

Desc. 60 ft. over NE. slope; through heavy green  
timber and dense undergrowth.

11.00 Ravine, course NE., asc. 150 ft. over SE. slope.

24.00 Spur, slopes NE., desc. 150 ft. over NE. slope.

30.00 Ravine, course NE., asc. 80 ft. over SE. slope.

40.00 Spur, slopes N.60\*E.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.