

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 2 E.

CHAINS


North 0*2'W., bet. secs. 21 and 22.

Desc. 10 ft. over NW. slope; through heavy green timber and dense undergrowth.

2.00 Ravine, course W., asc. 100 ft. over SW. slope.

33.35 Rock point, slopes W., asc. 30 ft. over SW. slope over small cliffs and slide rock.

38.85 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness cor. to 1/4 sec. cor., with brass cap mkd.



from which

A pine, 18 ins. diam., bears S.79*E., 48 lks. dist., mkd. WC 1/4 S22 B T

A cedar, 30 ins. diam., bears N.21*W., 11 lks. dist., mkd. WC 1/4 S21 B T

Asc. 90 ft. over SW. slope, over small cliffs and slide rock to spur.

40.00 Point for 1/4 sec. cor. falls on insecure ground.


46.00 Spur, slopes W., desc. 170 ft. over NW. slope.

53.30 Branch, 3 lks. wide, course W., asc. 295 ft. over SW. slope to the sec. cor.

62.50 Spring branch, 1 lk. wide, course SW.

80.00 Spur, slopes W.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 15,16,21 and 22, with brass cap mkd.



from which