

Subdivision of T. 28 S., R. 2 E.


CHAINS

North 0°2'W., on a true line bet. secs. 3 and 4.
Asc. 465 ft. along top of spur, slopes S., through heavy green timber and dense undergrowth.

22.40 Spur, slopes S. from NW. and spur, slopes E.
Desc. 65 ft. over NE. slope.

26.25 Ravine, course E., asc. 260 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which:

A cedar, 8 ins. diam., bears S.61°E., 36 lks.
dist., mkd. $\frac{1}{4}$ S3 BT.


A fir, 16 ins. diam., bears N.55°W., 39 lks.
dist., mkd. $\frac{1}{4}$ S 4 BT

Asc. 340 ft. over SE. slope.

73.59 Intersect the Sixth Standard Parallel South, 7.65 chs., West from the standard cor. of secs. 33 and 34, heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap mkd.



from which:

A fir, 20 ins. diam., bears S.17°E., 60 lks.
dist., mkd. T28S R2E S3 CC BT.

A fir, 26 ins. diam., bears S.17°W., 56 lks.
dist., mkd. T28S R2E S 4 CC BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd. rate.