

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 2 E.

CHAINS

73.79

Intersect the Sixth Standard Parallel South , 7.31 chs. West, from the standard cor. of secs. 32 and 33, heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap mkd.

T27S	R2E
S	32
S5	S4
T28S	R2E
C	C
1925	

from which:

A fir, 24 ins. diam., bears S.72 $\frac{1}{2}$ *E., 58 lks. dist., mkd. T28S R2E S4 CC BT.

A fir, 10 ins. diam., bears S.23*W., 14 lks. dist., mkd. T28S R2E S5 CC BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd. rate.

Timber, fir, pine and cedar.

Undergrowth, vine maple, rhododendron and chinquapin.

From the cor. of secs. 5,6,31 and 32, on S. bdy. of Tp., previously described in field notes of T.29 S., R. 2 E., this group.

North 0*4'W., bet. secs. 31 and 32.

Desc. 200 ft. over NE. slope; through heavy green timber and dense undergrowth.

20.40

Branch, 1 lk. wide, course NW., desc. 155 ft. over NW. slope.

36.60

Branch, 10 lks. wide, course N.30*W., thence over W. slope.