

Subdivision of T. 28 S., R. 2 E.

CHAINS

North 0*4'W., bet. secs. 29 and 30.

Asc. 140 ft. over SE. slope to spur; through heavy green timber and dense undergrowth.

12.05 Spring branch, 1 lk. wide, course SE.

21.75 Spur, slopes SE., desc. 45 ft. over NE. slope.

28.65 Branch, 2 lks. wide, course SE., asc. 200 ft. over SE. slope.

37.00 Spur, slopes SE., desc. 80 ft. over NE. slope.

40.00 Set a basalt, 24x10x8 ins., 18 ins. in the ground,

for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face., from which:

A fir, 26 ins. diam., bears N.53*E., 34 lks.

dist., mkd. $\frac{1}{4}$ S29 BT.

A hemlock, 14 ins. diam., bears N.18*W., 63 lks.

dist., mkd. $\frac{1}{4}$ S30 BT.

Desc. 25 ft. over NE. slope.

41.00 Branch, 2 lks. wide, course SE., asc. 85 ft. over SE. slope.

46.00 Spur, slopes SE., desc. 35 ft. over NE. slope.

48.75 Branch, 5 lks. wide, course SE., asc. 215 ft. over SE. slope.

65.75 Spur, slopes SE., desc. 15 ft. over NE. slope.

71.00 Branch, 3 lks. wide, course SE., asc. 85 ft. over SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 19,20,29 and 30, with brass cap mkd.

T28S	R2E	
S19	S20	
S30	S29	
1927		

from which:

A fir, 8 ins. diam., bears N.11*E., 22 lks.

dist., mkd. T28S R2E S20 BT.

A cedar, 10 ins. diam., bears S.5*E., 37 lks.

dist., mkd. T28S R2E S29 BT.