


Subdivision of T. 28 S., R. 2 E.

CHAINS

the ground, for cor. of secs. 17, 18, 19 and 20,
with brass cap mkd.



from which:

A pine, 12 ins. diam., bears N.14*E., 75 lks.
dist., mkd. T28S R2E S17 BT.

A fir, 26 ins. diam., bears S.66*E., 17 lks.
dist., mkd. T28S R2E S20 BT.

A pine, 20 ins. diam., bears S.75*W., 65 lks.
dist., mkd. T28S R2E S19 BT.

A pine, 8 ins. diam., bears N.5*W., 26 lks.
dist., mkd. T28S R2E S18 BT.

Land, mountainous.

Soil, loose, coarse, rocky loam; 3rd. rate.

Timber, fir, pine and cedar.

Undergrowth, vine maple, rhododendron and chinquapin.

South 89*59'E., on a random line bet. secs. 17 and 20.

40.00 Set temp. 1/4 sec. cor.

80.34 Intersect N. and S. line, 2 lks. S. of the cor. of
secs. 16,17, 20 and 21.

Thence

West, on a true line bet. secs. 17 and 20.

Asc. NE. slope; through heavy green timber and dense
undergrowth.

8.20 Spur, slopes SE. from W., trail, bears NW. and SE.
Thence along top of spur.

11.50 Trail, bears NE. and SW., spur, slopes S., continue
along top of spur, slopes E.

12.95 Trail, bears NW. and SE.

40.17 140 ft. above the sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for 1/4 sec. cor., with brass cap mkd.