

Subdivision of T. 28 S., R. 2 E.

CHAINS	
30.50	Spur, slopes S., desc. 10 ft. over SE. slope.
35.29	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
	the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S18
	S19
	1927
	from which:
	A fir, 46 ins. diam., bears N.56*W., 11 lks.
	dist., mkd. $\frac{1}{4}$ S18 BT.
	A fir, 60 ins. diam., bears S.15*E., 76 lks.
	dist., mkd. $\frac{1}{4}$ S 19 BT.
	Desc. 270 ft. over SE. slope.
43.65	Ravine, course S., asc. 60 ft. over SW. slope.
51.40	Spur, slopes S., desc. 295 ft. over SE. slope.
60.85	Ravine, course S., asc. 365 ft. over SW. slope.
75.29	The cor. of secs. 17, 18, 19 and 20.
	Land, mountainous.
	Soil, loose, coarse, rocky loam; 3rd. rate.
	Timber, fir, pine and cedar.
	Undergrowth, vine maple, rhododendron and chinquapin.
	North 0*4'W., bet. secs. 17 and 18.
	Asc. 220 ft. over SW. slope; through heavy green
	timber and dense undergrowth.
10.60	Spur, slopes SE., Five Lakes Trail, bears E. and W.
	Desc. 525 ft. over NE. slope.
26.20	Ravine, course E., asc. 60 ft. over SE. slope.
27.50	Spur, slopes E., desc. 60 ft. over NE. slope.
29.00	Branch, 1 lk. wide, course E., asc. 155 ft. over SE.
	slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
	the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.