


Subdivision of T. 28 S., R. 2 E.

CHAINS




From which:

A fir, 60 ins. diam., bears S.75*E., 36 lks.
dist., mkd. $\frac{1}{4}$ S17 BT.

A cedar, 12 ins. diam., bears S.63*W., 43 lks.
dist., mkd. $\frac{1}{4}$ S18 BT.

Asc. 15 ft. over SE. slope.

- 42.00 Spur, slopes E., desc. 195 ft. over NE. slope.
- 51.80 Branch, 2 lks. wide, course E., asc. 75 ft. over SE. slope.
- 58.00 Spur, slopes E., desc. 25 ft. over NE. slope.
- 62.50 Branch, 2 lks. wide, course SE., asc. 130 ft. over SE. slope.
- 68.00 Spur, slopes E., desc. 25 ft. over NE. slope.
- 75.15 Branch, 2 lks. wide, course E., asc. 45 ft. over SE. slope.
- 78.00 Spur, slopes E., desc. 25 ft. over NE. slope to the sec. cor.
- 79.35 Spring branch, 1 lk. wide, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 7,8,17 and 18, with brass cap mkd.



from which:

A yew, 12 ins. diam., bears N.32 $\frac{1}{2}$ *E., 25 lks.
dist., mkd. T28S R2E S8 BT.

A fir, 20 ins. diam., bears S.62*E., 51 lks.
dist., mkd. T28S R2E S17 BT.

A fir, 22 ins. diam., bears S.85*W., 35 lks.
dist., mkd. T28S R2E S18 BT.

A hemlock, 14 ins. diam., bears N.57*W., 45 lks.