


Subdivision of T. 28 S., R. 2 E.

CHAINS

North 0°4'W., on a true line bet. secs. 5 and 6.
 Desc. 205 ft. over NE. slope; through heavy green
 timber and dense undergrowth.

17.80 Branch, 5 lks. wide, course SE., asc. 475 ft. over
 SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which:

A fir, 78 ins. diam., bears S.87°E., 32 lks.
 dist., mkd. $\frac{1}{4}$ S5 BT.

A cedar, 12 ins. diam., bears S. 18°W., 25 lks.
 dist., mkd. $\frac{1}{4}$ S 6 BT.

Asc. 20 ft. over SE. slope.


42.00 Spur, slopes E., desc. 45 ft. over NE. slope.

44.25 Ravine, course E., asc. 235 ft. over SE. slope.

73.76 Intersect the Sixth Standard Parallel South, 7.31 chs.,
 West from the standard cor. of secs. 31 and 32,
 heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
 the ground, for closing cor. of secs. 5 and 6,
 with brass cap mkd.



from which:

A fir, 14 ins. diam., bears S.14°E., 72 lks.
 dist., mkd. T28S R2E S5 CC BT.

A fir, 24 ins. diam., bears S.46°W., 168 lks.
 dist., mkd. T28S R2E S6 CC BT.

Land, mountainous.