

Subdivision of T. 28 S., R. 2 E.

## CHAINS

Soil, loose, coarse, rocky loam; 3rd. rate.

Timber, fir, pine and cedar.

Undergrowth, vine maple, rhododendron and chinquapin.

7.35

To complete the survey of sec. 1, I go to the standard  $\frac{1}{4}$  cor. of sec. 36 on the S. bdy. of T. 27 S., R. 2 E., and run West, along S. bdy of sec. 36.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 1 only, with brass cap mkd.

—————  
 $\frac{1}{4}$  S1  
 1927

from which:

A pine, 24 ins. diam., bears S.80\*E., 45 lks.  
 dist., mkd.  $\frac{1}{4}$  S1 BT.

A pine, 24 ins. diam., bears S.88 $\frac{1}{2}$ \*W., 178 lks.  
 dist., mkd.  $\frac{1}{4}$  S 1 BT.

7.03

To complete the survey of sec. 2, I go to the standard  $\frac{1}{4}$  cor. of sec. 35 on the S. bdy. of T. 27 S., R. 2 E., and run West, along S. bdy. of sec. 35.

Set a basalt stone, 22x16x8 ins., 16 ins. in the ground, for witness cor. to  $\frac{1}{4}$  cor. of sec. 2 only, marked WC  $\frac{1}{4}$  S2 on S. face; from which

A fir, 30 ins. diam., bears S.1\*E., 44 lks.  
 dist., mkd. WC  $\frac{1}{4}$  S2 BT.

A fir, 30 ins. diam., bears S.14\*W., 130 lks.  
 dist., mkd. WC  $\frac{1}{4}$  S2 BT.

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,  
 E. of cor.

7.26

True point for cor. falls on exposed surface rock.