

Subdivision of T. 28 S., R. 2 E.

CHAINS

To complete the survey of sec. 3, I go to the standard $\frac{1}{4}$ cor. of sec. 34, on the S. bdy. of T. 27 S., R. 2 E., and run West, along S. bdy. of sec. 34.

7.41 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 3 only, with brass cap mkd.

 $\frac{1}{4}$ S3
1927

from which:

A fir, 20 ins. diam., bears S.44*E., 69 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

A fir, 8 ins. diam., bears S.16 $\frac{1}{2}$ *W., 37 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

To complete the survey of sec. 4, I go to the standard $\frac{1}{4}$ cor. of sec. 33, on the S. bdy. of T. 27 S., R. 2 E., and run West, along S. bdy. of sec. 33.

7.48 Falls on exposed surface rock, impracticable to establish cor.

7.52 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness cor. to $\frac{1}{4}$ sec. cor. of sec. 4 only, with brass cap mkd.

WC
 $\frac{1}{4}$ S4
1927

from which:

A fir, 14 ins. diam., bears S.65*E., 37 lks. dist., mkd. WC $\frac{1}{4}$ S4 BT.

A pine, 24 ins. diam., bears S.41 $\frac{1}{2}$ *W., 41 lks. dist., mkd. WC $\frac{1}{4}$ S4 BT.