

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 29 S., R. 3 E.
As surveyed by Herbert N. Raymond, U. S. C. E.
Under Special Instructions, dated Dec. 27, 1920.

CHAINS

From the cor. of Ts. 28 and 29 S., Rs. 3 and 4 E.
S.89°54'W., on a true line bet. secs. 1 and 36.

Over mountainous land, through heavy timber and medium
undergrowth.

Asc. 1300 ft. over broken SE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. deep
in small broken rock between boulders, for $\frac{1}{4}$ sec. cor.,
with brass cap marked

S 36
—
S 1
1927

from which

A fir, 14 ins. diam., bears N.25°E., 77 lks. dist.

Marked $\frac{1}{4}$ S 36 B T.

A fir, 10 ins. diam., bears S.26°W., 44 lks. dist.

Marked $\frac{1}{4}$ S 1 B T.

Asc. 350 ft. over broken SE. slope.

52.00 Top of a nearly perpendicular cliff, 100 ft. high, and
ridge, bears N. and S., sloping N. at this point;
desc. 125 ft. over rocky NW. slope.

62.00 Foot of desc. on N. slope; asc. 170 ft. over NE. slope.

79.25 Spur, slopes N., desc. 15 ft. over NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 1, 2, 35, and 36, with
brass cap marked

T 28 S | R 3 E
S 35 | S 36
S 2 | S 1
T 29 S
1927

from which

A larch, 20 ins. diam., bears N.60°E., 43 lks. dist.

Marked T 28 S R 3 E S 36 B T.

A larch, 22 ins. diam., bears S.47°E., 46 lks. dist.

Marked T 29 S R 3 E S 1 B T.

A larch, 18 ins. diam., bears S.8°W., 19 lks. dist.

Marked T 29 S R 3 E S 2 B T.