

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 29 S., R. 3 E.

CHAINS

A larch, 10 ins. diam., bears N.27\*W., 36 lks. dist.

Marked T 28 S R 3 E S 35 B T.

Land, mountainous.

Soil, rocky and sandy loam, third rate.

Timber, fir, pine, hemlock, larch, and cedar.

Undergrowth, willow, alder, huckle berry, and vine maple.

S.89\*54'W., on a true line bet. secs. 2 and 35.

Over mountainous land, through heavy timber and light undergrowth.

Desc. 545 ft. over NW. slope.

25.00 Forest Service Trail, bears NE. and SW.

33.35 Spring branch, 5 lks. wide, course NE., asc. 65 ft. over E. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in ground, to bed rock, and build a mound of stone, 2 ft. base, 1 ft. high, around the post, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$  S 35  


---

 S 2  
 1927

from which

A fir, 12 ins. diam., bears North, 26 lks. dist.

Marked  $\frac{1}{4}$  S 35 B T.

A pine, 28 ins. diam., bears S.15\*W., 35 lks. dist.

Marked  $\frac{1}{4}$  S 2 B T.

Asc. 310 ft. over E. and NE. slopes.

60.65 Spur, slopes N., desc. 740 ft. over W. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, in a small mound of stone, for cor. of secs. 2, 3, 34, and 35, with brass cap marked

T 28 S | R 3 E  
 S 34 | S 35  
 S 3 | S 2  
 T 29 S  
 1927