

## County Surveyor's Record, Douglas County, Oregon

Resurvey of Sixth Standard Parallel South through Range 3 E.  
and the Survey of E. Bdy. and Subdivisions of T. 28 S., R. 3 E.,  
As surveyed by Herbert N. Raymond, U. S. C. E.  
Under Special Instructions, dated Dec. 27, 1920.

## CHAINS

From the standard corner of Ts. 27 S., Rs. 2 and 3 E.,  
which is an iron post, 3 ins. diam., 9 ins. above  
ground, with brass cap marked and witnessed as  
described in the field notes of T. 28 S., R. 2 E.  
East, on S. bdy. of sec. 31.

Asc. 170 ft. over NW. slope, through medium timber and  
dense undergrowth.

5.40 Draw, drains NW., asc. 420 ft. over SW. slope.

22.15 Spur, slopes NW., desc. 75 ft. over NE. slope.

24.99 Spring branch, 1 lk. wide, course NW., asc. 110 ft. over  
SW. slope to  $\frac{1}{4}$  sec. cor. of sec. 6 only.

25.67 Old standard  $\frac{1}{4}$  sec. cor. of sec. 31 bears N. 3.07 chs. dist.  
Now obliterated.

34.45 Point 40.00 chs. in westing from the closing cor. of secs.  
5 and 6, determined as hereinafter described.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in ground,  
for  $\frac{1}{4}$  sec. cor. of sec. 6 only, with brass cap marked.

$\frac{1}{4}$  S 6  
1929

from which

A fir, 8 ins. diam., bears S.46\*E., 38 lks. dist.

Marked  $\frac{1}{4}$  S 6 B T.

A fir, 9 ins. diam., bears S.32\*W., 26 lks. dist.

Marked  $\frac{1}{4}$  S 6 B T.

Asc. 15 ft. over NW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
ground, for standard  $\frac{1}{4}$  sec. cor. of sec. 31, with  
brass cap marked

S C  
 $\frac{1}{4}$  S 31  
1929

from which

A pine, 24 ins. diam., bears N.39\*E., 35 lks. dist.

Marked S C  $\frac{1}{4}$  S 31 B T.

A fir, 10 ins. diam., bears N.1 $\frac{1}{2}$ \*W., 43 lks. dist.