

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

Marked S C $\frac{1}{2}$ S 31 B T.

Desc. 15 ft. over NE. slope.

44.00 Swale, drains NW., asc. 190 ft. over NW. slope.

63.00 Spur, slopes N., desc. 10 ft. over NE. slope.

65.50 Draw, drains NW., asc. 150 ft. over SW. slope to C C.

66.09 Old standard cor. of secs. 31 and 32, bears N. 3.88 chs. dist.

Now obliterated.

74.45 Point of intersection of the line bet. secs. 5 and 6, determined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap marked

```

T 27 S R 3 E
  S 31
-----
  S 6 S 5
T 28 S R 3 E
  C C
  1929
    
```

from which

A fir, 36 ins. diam., bears S.23*E., 46 lks. dist.

Marked C C T 28 S R 3 E S 5 B T.

A fir, 9 ins. diam., bears S.70*W., 18 lks. dist.

Marked C C T 28 S R 3 E S 6 B T.

Asc. 120 ft. over NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in ground, to bed rock, and raise a mound of stone, 2 ft. base, 1 ft. high around the post, for standard cor. of secs. 31 and 32, with brass cap marked

```

          S C
T 27 S R 3 E
  S 31 S 32
-----
T 28 S R 3 E
  S 5
  1929
    
```

from which

A fir, 17 ins. diam., bears N.76*E., 72 lks. dist.

Marked S C T 27 S R 3 E S 32 B T.