

County Surveyor's Record, Douglas County, Oregon

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

A fir, 12 ins. diam., bears N.47*W., 15 lks. dist.

Marked S C T 27 S R 3 E S 31 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 2nd. and 3rd. rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, rhododendron, huckleberry, willow, small
yew, fir, and hemlock.

East, on S. bdy. of sec. 32.

Asc. slightly over W. slope, through heavy timber and
medium undergrowth.2.00 Spur ridge, bears NE. and SW., desc. 20 ft. over SE.
slope.

10.00 Draw, drains S., asc. 85 ft. over SE. slope.

26.23 Old standard $\frac{1}{4}$ sec. cor. of sec. 32, bears N.3.52 chs.
dist.

Now obliterated.

26.90 Spur, slopes S., desc. 95 ft. over NE. slope to next $\frac{1}{4}$
sec. cor.

34.31 Trail, bears NE. and SW.

34.65 Mid point bet. NE. and NW. corners of sec. 5, determined
as hereinafter described.Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in
ground, to bed rock, and raise a mound of stone, 2 ft.
base, 1 ft. high, around the post, for $\frac{1}{4}$ sec. cor.
of sec. 5 only, with brass cap marked
$$\frac{1}{4} \text{ S } 5$$
 1929

from which

A fir, 36 ins. diam., bears S.49*E., 37 lks. dist.

Marked $\frac{1}{4}$ S 5 B T.

A fir, 30 ins. diam., bears S.18*W., 35 lks. dist.

Marked $\frac{1}{4}$ S 5 B T.Desc. 70 ft. over SE. slope to S C $\frac{1}{4}$ sec. cor.