

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

34.75

Draw, drains SE., 2.25 chs. NW. from a good spring.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in ground, for standard $\frac{1}{4}$ sec. cor. of sec. 32, with brass cap marked

S C
 $\frac{1}{4}$ S 32
1929

from which

A fir, 24 ins. diam., bears N.52*E., 33 lks. dist.

Marked S C $\frac{1}{4}$ S 32 B T.

A fir, 20 ins. diam., bears N.52*W., 35 lks. dist.

Marked S C $\frac{1}{4}$ S 32 B T.

Desc. 45 ft. over SE. slope.

41.60

Spring branch, 1 lk. wide, course SE., asc. 160 ft. over SW. slope.

49.60

Spur, slopes S., desc. 50 ft. over SE. slope.

56.52

Creek, 3 lks. wide, course SE., thence over S. slope.

62.51

Creek, 4 lks. wide, course S., asc. 155 ft. over SW. slope to C C.

66.25

Old standard cor. of secs. 32 and 33, bears N. 3.25 chs. dist.

Now obliterated.

74.85

Point of intersection of the line bet. secs. 4 and 5, determined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap marked

T 27 S R 3 E
S 32
S 5 S 4
T 28 S R 3 E
C C
1929

from which

A fir, 20 ins. diam., bears S.50*E., 34 lks. dist.

Marked C C T 28 S R 3 E S 4 B T.

A fir, 20 ins. diam., bears S.34*W., 65 lks. dist.

Marked C C T 28 S R 3 E S 5 B T.