

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

from which

A pine, 16 ins. diam., bears S.42*E., 14 lks. dist.

Marked $\frac{1}{4}$ S 4 B T.

A larch, 20 ins. diam., bears S.54*W., 58 lks. dist.

Marked $\frac{1}{4}$ S 4 B T.

Desc. 100 ft. over NE. slope to S C $\frac{1}{4}$ S 33, enter dense 2nd. growth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in ground, for standard $\frac{1}{4}$ sec. cor. of sec. 33, with brass cap marked

S C
 $\frac{1}{4}$ S 33
1929

from which

A fir, 24 ins. diam., bears N.23*W., 40 lks. dist.

Marked S C $\frac{1}{4}$ S 33 B T.

A fir, 30 ins. diam., bears N.67*W., 50 lks. dist.

Marked S C $\frac{1}{4}$ S 33 B T.

Desc. 370 ft. over NE. slope.

58.54 Spring branch, 3 lks. wide, course N., asc. 30 ft. over SW. slope.

65.67 Old standard cor. of secs. 33 and 34, bears N. 3.53 chs. dist. Now obliterated.

67.40 Spur, slopes N., desc. 75 ft. over NE. slope to C C.

72.13 Spring branch, 3 lks. wide, course NE.

74.84 Point of intersection of the line bet. secs. 3 and 4, determined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bed rock, and raise a mound of stone, 2 ft. base, 1 ft. high, around the post, for closing cor. of secs. 3 and 4, with brass cap marked

T 27 S R 3 E
S 33
S 4 S 3
T 28 S R 3 E
C C
1929